

Features and Benefits:

- Low power consumption
- Supports 1D, 2D, and composite codes
- Will read codes on mobile phone LCD screens
- Omnidirectional reading
- Auto-sensing mode

2DScan™

Handheld 2D Barcode Imager

Global 1D and 2D Symbology Reading

The ID TECH 2DScan is a well-designed handheld scanner for 1D and 2D barcode scanning for retail, logistics, and office automation. With the increasing popularity of 2D barcodes, the 2DScan ensures readability of most global symbologies.

Superior Reading Performance

With the high-performance CMOS scan engine, the 2DScan can be used to scan barcodes off of LCD displays such as cell phones and monitors, as well as surfaces in bright sunlight. The imaging technology also allows the 2DScan to capture the barcode omnidirectionally regardless of its orientation, which improves productivity and efficiency in a wide range of applications.

Flexible Compatibility

With the interchangeable PS/2, RS232 and USB Keyboard cables, the 2DScan provides excellent flexibility and ease of use. The 2DScan is a plug-and-play device that allows for operation right out of the box.





2DScan FX100

Specifications IDBA-66X2LRB

Electrical

Power Requirements: 5.0 VDC +/-5%

Interfaces: PS/2, RS232 and USB Keyboard

Light Source: 630 nm visible red LED

Sensor: CMOS

Environmental

 $\begin{array}{ll} \mbox{Operating Temperature:} & 23^{\circ}\mbox{F to } 113^{\circ}\mbox{F (}-5^{\circ}\mbox{C to } 45^{\circ}\mbox{C)} \\ \mbox{Storage Temperature:} & -40^{\circ}\mbox{F to } 140^{\circ}\mbox{F (}-40^{\circ}\mbox{C to } 60^{\circ}\mbox{C)} \\ \mbox{Humidity:} & 5\%-95\% \ \ \mbox{relative humidity} \\ \end{array}$

Drop Test: 4.92 feet (1.5 m)

Mechanical

Dimension (L)x(W)x(H): 6.46 inches (164 mm) x 4.96 inches (126 mm) x 2.87 inches (73 mm)

Weight: 8.82 oz.
Indicators: LED, beep tone
Color: Black with grey detail

Field Width: 5.12 inches (130 mm) for 10 mil code 39 at 200 mm from the lens plate

Resolution: 752 x 480
PCS: 25% or more
Scan Rate: 60 frames per second

oo nunes per second

Range: 1.77 inches (45 mm) to 17.72 inches (450 mm)

2D Symbologies: PDF417, QR Code (Model 1/2), DataMatrix (ECC200, ECC000, 050, 080,

100, 140), Aztec, Chinese-Sensible Code, Maxicode, LP Code etc.

1D Symbologies: Code128, EAN-13, EAN-8, Code39, UPC-A, UPC-E, Codabar, China post 25,

Interleaved 2 of 5, ISBN/ISSN, Code93, etc.

Approvals: FCC Part 15 Class B, CE EMC Class B

10721 Walker Street

United States Sales Office

Cypress, CA 90630 Phone: (714) 761-6368 Toll Free:(800) 984-1010 Fax: (714) 761-8880

sales@idtechproducts.com

Corporate Headquarters

International Sales Offices

Asia

+866-3-496-6988 (Taiwan) asia@idtechproducts.com.tw

Canada

+450-465-5261

robertop@idtechproducts.com

South America

+55-11-3079-2255

internationalsales@idtechproducts.com

Europe

Germany & United Kingdom emea@idtechproducts.com

ISO 9001 Certified

Test Codes:

Code39



PDF417



OR Code



UPC-A



Value through Innovation

