

PRELIMINARY

VP3350

3-IN-ONE CARD READER FOR CONTACTLESS & MOBILE

The VP3350 is ID TECH's most robust mobile reader. It is PCI PTS SRED 6.X certified & has the latest in device hardware protection ensuring secure payment transactions. With rotating USB-C connector, Apple lightning connector & Bluetooth connections, the VP3350 can connect to all mobile merchant Android & iOS devices & can be integrated into a stand for support of traditional countertop POS systems. The VP3350 supports all contactless payment methods including Google Pay, Apple Pay & Samsung Pay along with supporting the loyalty programs Apple VAS and Google SmartTap 2.1.



**Bluetooth model shown*



✉ 10721 Walker Street
Cypress, CA 90630

☎ (714) 761-6368
✉ sales@idtechproducts.com

🌐 www.idtechproducts.com

NEO 3

PLATFORM OF PRODUCTS

ONE COMMON KERNEL.

ONE INTEGRATION.

MULTIPLE ENVIRONMENTS.

SUPPORTS SMART MSR, CHIP & CONTACTLESS PAYMENTS

Using ID TECH's NEO 3.0 Platform, the VP3350 uses our Common L2 Kernel & has family contactless certification allowing for support with other NEO 3.0 products.

CONTACT US TODAY!

CORPORATE HEADQUARTERS

10721 WALKER STREET
CYPRESS, CA 90630
TEL: (714) 761-6368
TF: (800) 984-1010
SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA

(714) 761-6368
SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

PRELIMINARY VP3350 SPECS

BATTERY	Minimum 400 contactless transactions on full charge or 500 EMV transactions on full charge or 800 MSR transactions on full charge
CERTIFICATIONS	PCI PTS 6.X SRED
CONTACTLESS CARD READER	ISO 14443 Type A&B, Mifare, ISO 18092 P2P, Visa pay, Mastercard, AMEX, Discover, Apple Pay, Apple VAS, Google Pay, Google SmartTap 2.1 and Samsung Pay, Sony FeliCa
DIMENSIONS	67mm (H) x 71mm (W) x 13.5mm (D)
EMV CONTACT	Part of ID TECH's Common Kernel
ENCRYPTION	AES 128, RSA Transarmor, TDES Transarmor, TDES
HUMIDITY	5% to 95% Non-Condensing
INTERFACE	USB HID, Bluetooth Low Energy, Apple Lightning
KEY MANAGEMENT	DUKPT
OPERATING TEMPS	0°C to 55°C (32°F to 131°F)
STORAGE TEMPS	-20°C to 60°C (-4°F to 140°F)
SMART CARD READER	500,000 Inserts
WARRANTY	1 Year Manufacturer Warranty

ISO 9001 CERTIFIED
ISO 14001 CERTIFIED

