



# Xpress CM 100™

## Contactless Reader Module

### Contactless Technology

The Xpress CM100 reads card data from a variety of contactless sources, including credit cards, key fobs, and NFC-enabled cell phones. It is designed for POS applications that accept contactless transactions, such as quick-service venues and self-service kiosks. Four LED indicators at the top of the module make it easy for cardholders to see that they have completed a successful card read operation.

### Easy to Integrate


The Xpress CM100 is designed to allow flexibility of integration of EMV 2.0.1 contactless card reading to different market segments. With its modular architecture, the reader can be mounted to kiosks, attached to terminals, or used as a countertop standalone device. It is also possible to integrate the module with other payment technologies, such as MagStripe readers. The Xpress CM100 is an optional attachment for the ID TECH Sign&Pay terminal.

### Versatility

The Xpress CM100 is perfect for a wide variety of applications, including quick service restaurants, ticket booths, parking garages, retail locations, public transportation, and gas stations. With support for Visa payWave, MasterCard PayPass, American Express ExpressPay, Discover Zip and MiFare and NFC technologies, the Xpress CM100 can be integrated into just about any application that accepts contactless technology.

## Features and Benefits:

- Reads data from contactless cards, key fobs, and cell phones
- Compact design: Small footprint is ideal for flexible integration
- Complies with EMV Contactless 2.0.1
- Clear identification of successful card reads with LED indicators
- Compatible with ID TECH Sign&Pay terminal
- Certified by:
  - Visa payWave
  - MasterCard PayPass
  - American Express ExpressPay
  - Discover card Zip



# Xpress CM 100™

## Specifications IDCA-1261

### Electrical

Power Requirements: +5 VDC  
Interface: USB-HID

### Environmental

Operating Temperature: -4°F to 158°F (-20°C to 70°C)  
Storage Temperature: -40°F to 176°F (-40°C to 70°C)  
Humidity: Maximum 95% non-condensing, dry storage



### Reliability

Conformance: ISO 14443 Type A & B  
Warranty: One year, parts and labor

### Mechanical

Dimension (L)x(W)x(H): 0.59 inches (15mm) x 3.71 inches (94.2mm) x 2.96 inches (75.2mm)  
Weight: 1.92 oz. (4.78 oz. with cable)  
Indicators: Four LED lights and beeper  
Cable Length: 3 feet (0.91m)

Footprint:



### United States Sales Office

#### Corporate Headquarters

10721 Walker Street  
Cypress, CA 90630  
Phone: (714) 761-6368  
Toll Free: (800) 984-1010  
Fax: (714) 761-8880  
sales@idtechproducts.com

### International Sales Offices

#### Asia

+866-3-496-6988 (Taiwan)  
asia@idtechproducts.com.tw

#### Canada

+450-465-5261  
robertop@idtechproducts.com

#### South America

+55-11-3079-2255  
internationalsales@idtechproducts.com

#### Europe

Germany & United Kingdom  
emea@idtechproducts.com

### ISO 9001 Certified



Value through Innovation

www.idtechproducts.com