



VP3350

3-IN-ONE CARD READER FOR CONTACTLESS & MOBILE

The VP3350 is ID TECH's most robust mobile reader. It is PCI PTS SRED 6.X certified & has the latest in device hardware protection ensuring secure payment transactions. With rotating USB-C connector, Apple lightning connector & Bluetooth connections, the VP3350 can connect to all mobile merchant Android & iOS devices & can be integrated into a stand for support of traditional countertop POS systems. The VP3350 supports all contactless payment methods including Google Pay, Apple Pay & Samsung Pay along with supporting the loyalty programs Apple VAS and Google SmartTap 2.1.



**Bluetooth & USB-C models available*

Made for
iPhone | iPad



10721 Walker Street
Cypress, CA 90630

(714) 761-6368
sales@idtechproducts.com

www.idtechproducts.com

NEO 3

PLATFORM OF PRODUCTS

ONE COMMON KERNEL.

ONE INTEGRATION.

MULTIPLE ENVIRONMENTS.

SUPPORTS SMART MSR, CHIP & CONTACTLESS PAYMENTS

Using ID TECH's NEO 3.0 Platform, the VP3350 uses our Common L2 Kernel & has family contactless certification allowing for support with other NEO 3.0 products.

CONTACT US TODAY!

CORPORATE HEADQUARTERS

10721 WALKER STREET
CYPRESS, CA 90630
TEL: (714) 761-6368
TF: (800) 984-1010
SALES@IDTECHPRODUCTS.COM

ASIA

+886-3-326-5988 (TAIWAN)
ASIA@IDTECHPRODUCTS.COM

LATIN AMERICA

(714) 761-6368
SALES@IDTECHPRODUCTS.COM

EUROPE, MIDDLE EAST & AFRICA

EMEA@IDTECHPRODUCTS.COM

VP3350 SPECS

BATTERY	Li-Polymer Battery 400mAh (for BT & Lightning Models)
BATTERY LIFE	800 MSR Transactions 500 Contact Transactions 400 Contactless Transactions 200 Contactless + 200 Contact + 100 MSR Transactions
CERTIFICATIONS	PCI PTS 6.X SRED , EMV Contact L1&L2, EMV Contactless L1, Visa, Mastercard, Amex, Discover, Mastercard TQM, Apple Pay, Google Pay, Samsung Pay, Felica, Interact, Interact Transit, FCC, CE, RohS
DIMENSIONS	67mm (H) x 71mm (W) x 13.5mm (D)
ENCRYPTION	AES 128, TDES, Transarmor
FUNCTIONS	Contactless Card Reader EMV Chip Card Reader Field Upgradeable Firmware Passthrough Charging SMART MSR (Reads up to 3 Tracks)
INTERFACE	BLE, Lightning, USB-C
KEY MANAGEMENT	DUKPT
OPERATING TEMPS	0°C to 55°C (32°F to 131°F)
STORAGE TEMPS	-20°C to 60°C (-4°F to 140°F)

ISO 9001 CERTIFIED
ISO 14001 CERTIFIED

